

About

"Built to Protect. Made to Last."

We're Cobrashield, born from over 20 years of hands-on experience with Cobra Wrap Tools Group Australia.

Our passion for wraps, tints, and detailing led us to create a product line made just for the real-world needs of Aussie and U.S. pros.

From paint protection and window tint films to ceramic coatings, every product we offer is designed to perform, priced to help you stay profitable, and backed by the knowledge of people who've been in the industry for decades.

We get what you do—because we've done it too.

Products

Window Tinting Films

Clear PPF

Windshield PPF

Sunroof PPF

Carbon Fiber PPF

Headlight PPF

Warranty

PPF

COBRASHIELD will cover defects in the products, such as degumming, cracking, blistering, and delaminating. This Limited Warranty does not cover defects caused by external factors, including but not limited to physical impact from rocks or road debris, chemical abuse (e.g., harsh cleaners and solvents), thermal abuse or shock (e.g., excessive heat or cold), misuse, collision, accidental damage, air conditioner water drops, fire, hail, flood, surface rust, rail dust, physical damage, paint overspray, etc.

The warranty period for COBRASHIELD ar paint protection film varies depending on the specific product series.

TINTING FILMS

COBRASHIELD provides a limited lifetime warranty covering defects in manufacturing, including fading, peeling, cracking, delaminating, and adhesive failure. This warranty does not extend to damages or issues resulting from improper installation.

CARE

PPF CARE

- *Avoid driving at high speeds within 3 days after installation.*
- *Avoid car washing for one week (7 days) to ensure the best adhesion between the glue and the paint surface.*
- *Avoid using a pressure washer or high-pressure water near the edges of the film, as it can cause the film to lift and/or become damaged.*
- *Avoid scratching or wiping the film surface with hard objects, as scratches and abrasion marks will affect the overall appearance of the film.*
- *Areas exposed to acid rain, air conditioning water, acidic or alkaline liquids, or slight scratches are not covered by the warranty. Please contact us immediately.*
- *Car detailing and maintenance are recommended twice a year.*

TINT CARE

For the first two days following the application, keep all windows fully closed to allow the film to properly settle.

Refrain from washing the glass during the initial drying period, which typically takes around three weeks.

Right after installation, the film may appear cloudy or have small pockets of moisture. This is part of the normal bonding process and will clear up as the material sets—although cooler temperatures can extend this period.

Even after everything has fully dried, tiny dust particles or faint marks may still be visible when viewed from outside the vehicle. These are a natural result of the adhesive process and won't impact how the tint functions or cause future bubbling.

To clean the surface, gently wipe using a microfiber cloth or soft towel paired with a non-ammonia-based glass cleaner, such as Black Armor or similar products. Stay away from anything abrasive, including rough cloths, scrubbing tools, powdered cleaners, or solutions containing ammonia.

Be mindful when releasing your seatbelt, as it may snap back and strike the window, potentially scratching the surface. Use caution when placing items in your car to avoid scuffing or damaging the tinted areas.